


**LABEL INFORMATION**  
 APES11M-8-004ZY  
 2.56V 1.0A  
 ElectroCraft  
 XXXX XXXXXX RoHS

DATE CODE SERIAL NUMBER

BIPOLAR SPECIFICATIONS	
RATED VOLTAGE (Vm) DC	2.56
AMPS/PHASE	1.0
RESISTANCE/PHASE Rm (OHMS)	2.56
INDUCTANCE/PHASE (MH @ 1000Hz)	1.85
STEP ANGLE (DEGREES)	1.8
STEP ACCURACY (NON-ACCUM)%	±5
HOLDING TORQUE (N.cm)	8
ROTOR INERTIA (g-cm <sup>2</sup> )	13.3
WEIGHT (Kg)	0.16

NOTES:  
 5. LINEAR TRAVEL PER STEP: 0.0120mm.



**FULL STEP SEQUENCE  
 2 PHASE ON**

STEP	A	A'	B	B'
1	+	-	+	-
2	+	-	-	+
3	-	+	+	-
4	-	+	-	+

CW ROT'N (LEAD END)

P01	FISRT ISSUE			Sam Yu	07/29/2016
REV	ECN NO.	DESCRIPTION		BY	DATE
SCALE 1:1	SHEET 1 OF 1	DWN BY Sam Yu	DATE 06/24/2016	ROHS YES	CONFIDENTIAL INFORMATION OF ELECTROCRAFT
CUSTOMER	CUSTOMER P/N	CHK BY	DATE	QTY 1	
UNLESS OTHERWISE SPECIFIED		APRV BY	DATE	A4	TITLE LEADSCREW MOTOR
1. ISO 2768-1 CLASS m		OUTLINE/ASSY NO.	FINISH BLACK LAM		DWG NO. APES11M-8-004ZY
2. DIMENSION UNIT: mm					ECNH P/N:
3. CPK:					
SYMBOL		CPK			
●		>2.0			
●		>1.67			
●		>1.33			
●		NO SPEC.			

深圳市汇升睿控  
 科技有限公司